

GOES-17 ABI Fire Detection and Characterization (FDC) Release
Beta Data Quality
October 11, 2018
Read-Me for Data Users

The GOES-17 Advanced Baseline Imager (ABI) L2+ Fire Detection and Characterization (FDC) product was declared Beta maturity on August 27, 2018. No formal review was conducted because the algorithms are identical to the ones running with GOES-16, so the Beta declaration of the ABI L1b and CMI flows down to the ABI L2+ products.

The ABI L2+ FHS consists of four product outputs: metadata mask, fire radiative power (FRP), instantaneous fire temperature, and instantaneous fire size. The metadata mask assigns a flag to every earth-navigated pixel that indicates its disposition with respect to the FHS algorithm. It includes six fire categories:

- Processed fire: The highest fire confidence category, includes FRP, size, and temperature estimates
- Saturated fire: Also very high confidence fires, but the pixel was at instrument saturation so no properties could be determined
- Cloudy fire: A high confidence fire that appears to be partially obscured by cloud
- High possibility fire: A likely fire that did not meet the thresholds for the Processed category
- Medium possibility fire: Medium confidence fire category
- Low possibility fire: The lowest confidence class, a large number of false alarms are to be expected, also contains small and/or cooler fires

Each of the fire categories has a temporally filtered equivalent, which is triggered if fire was found within +/-1 pixel in the last 12 hours. Also included in the mask are flags that indicate why a pixel was excluded from consideration, including due to water, certain surface types, clouds, and bad data.

The FRP, size, and temperature fields represent the properties of a fire that would produce the same detected radiant energy for the pixel. Fires vary throughout their burn area in intensity, but the satellite measurement is a composite signal of the entire pixel. FRP, size, and temperature represent the composite properties of that pixel. A hypothetical fire with those properties would produce the same measured radiances. Due to this mixing of subpixel elements and diffraction in the sensor there are large error bars on these retrievals.

The FHS products are generated for every ABI Full Disk (FD) of the Earth and CONTiguous United States (CONUS) region. They are not generated for the Mesoscale (MESO) regions.

A full description and format of the FHS product can be found in the Product Definition and User's Guide (PUG) document (<http://www.goes-r.gov/products/docs/PUG-L2+-vol5.pdf>). The algorithm used to derive the FHS products from GOES-17 ABI observations is described in detail in the "GOES-R Advanced Baseline Imager (ABI) Algorithm Theoretical Basis Document for Fire / Hot Spot Characterization" (<https://www.goes-r.gov/products/ATBDs/baseline/baseline-fire-hot-spot-v2.0.pdf>).

Beta maturity, by definition, means that:

- Rapid changes in product input tables / algorithms can be expected;
- Product quick looks and initial comparisons with ground truth data were not adequate to determine product quality;
- Anomalies may be found in the product and the resolution strategy may not exist;
- Product is made available to users to gain familiarity with data formats and parameters;
- Product has been minimally validated and may still contain significant errors; and
- Product is not optimized for operational use.

Beta users bear all responsibility for inspecting the data prior to use and for the manner in which the data are utilized. Persons desiring to use the GOES-17 ABI Beta maturity Fires products for any reason, including but not limited to scientific and technical investigations, are encouraged to consult the NOAA algorithm working group (AWG) for feasibility of the planned applications. These products are sensitive to upstream processing, specifically the quality of the calibration and navigation.

Known issues at this stage include:

1. Missing values occur randomly due to upstream L1b issues, typically in the form of rectangular blocks;
2. False alarms are known to occur due to relatively solitary water clouds (i.e. surrounded by ice clouds or cloud free ground) causing reflections that appear fire-like, particularly at high solar zenith angles;
3. False alarms due to surface heterogeneity, such as bare ground surrounded by vegetated fields, power plant cooling lakes, urban areas that are not properly screened out, coastlines, and others, are known to occur and tend to recur in the same locations at certain times of year – these most frequently manifest as low possibility and processed fires;
4. Co-registration errors in the L1b data between bands 7 and 14 can lead to numerous false alarms, particularly during the daytime hours and often manifesting as false alarms that follow geographic features;
5. Due to the failure of active cooling of the ABI sensor, L1b data quality is degraded around satellite midnight, particularly around the vernal and autumnal equinoxes. This leads to errors in the FDC mask product and impacts fire detections causing them to change classifications or completely disappear. The data is only useful for qualitative analysis at best during those times;
6. A known processing error in the cloud mask causes over-estimates of cloud cover over cold ground and was observed frequently early in Spring 2018. This affects the quality of the cloud mask and the detections of some fires in those regions;
7. The temporal filtering is not functioning properly and those pixels should be treated the same as the other fire pixels;

8. Detections and characterizations will differ between satellites, even when they contain the same instruments, due to viewing geometry and surface topography.

Please report any systematic false alarms and other concerns to the AWG FHS science team.

Contact for further information: OSPO User Services at SPSD.UserServices@noaa.gov

AWG scientist contacts for specific information on the ABI L2 FHS product:

Chris Schmidt: chris.schmidt@ssec.wisc.edu

Ivan Csiszar: ivan.csiszar@noaa.gov

Wilfrid Schroeder: wilfrid.schroeder@noaa.gov